



STORACE 蓄雷

Store energy Release passion

Guangzhou Xuntian Electronic Technology Co., Ltd

※Introduction

Guangzhou Xuntian Electronic Technology Co., Ltd is located in beautiful flower city----Guangzhou Guangdong province, China. Our company is a high new technical company, and we focus on research and development of lead acid battery, deep cycle battery and Gel storage battery. Beside, we sale full range of different capacity 12 voltage,6 voltage or 2 voltage battery.



Storage Battery is used mainly in UPS electric power; telecommunication; solar or wind power system; aerospace and navigation; bank and medical system; rail transit; military area and so on.



After years of development, we built up a professional product research and develop term, and a mature engineering technology research centre. With such facility and domestic famous senior engineers of battery production as consultant, our technology is leading in battery production field.



Our researched and developed storage battery earned a high reputation not only in China but also in all over the world. Our batteries sale to European market; American market; Southeast Asia market; Africa market and Middle East market, what is more, they all received high compliment from customer.





※ VALVE REGULATED LEAD ACID BATTERY

Application

- Control systems
- Electric toys
- Emergency lamp
- UPS
- Firefighting Equipment
- Standby power supply
- Power tools
- Alarm system
- Power system
- Medical Equipment
- Telephone switching system
- Telecommunication system
- Railway station
- Ship Equipment
- Military Equipment
- Emergency light

Characteristics

- Excellent safety performance
- Good discharging performance
- Good stock-proof performance
- Good impact-proof performance
- Good resistance to over discharge
- Good resistance to overcharge
- Good resistance to high current



From 0.8Ah to 28Ah

电池型号 Battery Model	额定 电压 Nomina l voltage (V)	容量 (Ah) Ratedca pacity (Ah) 20hrs/2 5°C	重量约 Approx. weight		外观尺寸 Dimension								端子 类型 Terminal Type
			kg	lbs	长 Length		宽 Width		高 Height		Total Height		
					mm	inch	mm	inch	mm	inch	mm	inch	
SR1.0-6	6	1.0	0.26	0.57	51	2.01	42	1.65	51	2.01	57	2.24	T0
SR1.3-6	6	1.3	0.31	0.68	98	3.86	25	0.99	52	2.05	56	2.21	T0
SR3.3-6	6	3.3	0.63	1.39	134	5.28	34	1.34	61	2.40	66	2.60	T0
SR4-6	6	4	0.66	1.46	70	2.76	48	1.89	101	3.98	106	4.18	T1
SR4-6	6	4	0.69	1.52	70	2.76	48	1.89	101	3.98	106	4.18	T1
SR4.2-6	6	4.2	0.72	1.59	70	2.76	48	1.89	101	3.98	106	4.18	T1
SR4..5-6	6	4.5	0.72	1.59	70	2.76	48	1.89	101	3.98	106	4.18	T1
SR5-6	6	5	0.78	1.72	70	2.76	48	1.89	101	3.98	106	4.18	T1
SR5-6	6	5	0.85	1.87	70	2.76	48	1.89	101	3.98	106	4.18	T1



SR6-6	6	6	1.00	2.20	85	3.35	48	1.89	100	3.94	105	4.14	T1
SR7-6	6	7	1.10	2.43	151	5.95	34	1.34	94	3.70	100	3.94	T1
SR8-6	6	8	1.28	2.82	151	5.95	34	1.34	94	3.70	100	3.94	T1
SR9-6	6	9	1.60	3.53	99	3.90	56	2.21	118	4.65	118	4.65	T1
SR10-6	6	10	1.65	3.64	151	5.95	50	1.97	94	3.70	100	3.94	T1
SR12-6	6	12	1.81	3.99	151	5.95	50	1.97	94	3.70	100	3.94	T1
SR14-6	6	14	2.30	5.06	107	4.21	70	2.76	140	5.55	140	5.55	TW10
SR0.8-12	12	0.8	0.32	0.71	96	3.78	25	0.98	62	2.44	62	2.44	T21
SR1.2-12	12	1.2	0.55	1.21	98	3.86	45	1.77	52	2.05	59	2.32	T0
SR1.9-12	12	1.9	0.90	1.98	178	7.01	34	1.34	60	2.36	66	2.60	T0
SR2.0-12	12	2.0	0.58	1.28	144	5.67	23	0.91	64	2.52	64	2.52	T23
SR2.3-12	12	2.3	0.90	1.98	178	7.01	34	1.34	60	2.36	66	2.60	T0
SR2.6-12	12	2.6	0.74	1.63	70	2.76	47	1.85	98	3.86	103	4.06	
SR2.9-12	12	2.9	1.05	2.32	79	3.11	56	2.21	99	3.90	104	4.10	
SR3.3-12	12	3.3	1.24	2.73	134	5.28	67	2.64	60	2.36	66	2.60	T0
SR4-12	12	4	1.33	2.93	90	3.55	70	2.76	101	3.98	106	4.18	T1
SR4.5-12	12	4.5	1.38	3.04	140	5.52	48	1.89	102	4.02	104	4.10	T1,T2
SR4.5-12	12	4.5	1.47	3.24	90	3.55	70	2.76	101	3.98	106	4.18	T1
SR5-12	12	5	1.70	3.75	151	5.95	51	2.01	94	3.70	100	3.94	T1
SR7-12	12	7	2.10	4.63	151	5.95	65	2.56	94	3.70	100	3.94	T2
SR7.2-12	12	7.2	2.20	4.85	151	5.95	65	2.56	94	3.70	100	3.94	T2
SR7.5-12	12	7.5	2.35	5.18	151	5.95	65	2.56	94	3.70	100	3.94	T1
SR8-12	12	8	2.35	5.18	151	5.95	65	2.56	94	3.70	100	3.94	T1
SR9-12	12	9	2.50	5.51	151	5.95	65	2.56	94	3.70	100	3.94	T1
SR10-12	12	10	2.95	6.50	151	5.95	65	2.56	111	4.37	116	4.57	T2
SR10-12	12	10	3.10	6.83	151	5.95	98	3.86	94	3.70	100	3.94	T2
SR12-12	12	12	3.43	7.56	151	5.95	98	3.86	94	3.70	100	3.94	T2
SR12-12	12	12	3.76	8.29	151	5.95	98	3.86	94	3.70	100	3.94	T2
SR14-12	12	14	3.65	8.05	151	5.95	98	3.86	94	3.70	100	3.94	T2
SR15-12	12	15	4.85	10.69	181	7.13	77	3.03	167	6.58	167	6.58	T3
SR17-12	12	17	5.00	11.02	181	7.13	77	3.03	167	6.58	167	6.58	T3
SR18-12	12	18	5.00	11.02	181	7.13	77	3.03	167	6.58	167	6.58	T3
SR20-12	12	20	5.50	12.13	181	7.13	77	3.03	167	6.58	167	6.58	T3
SR24-12	12	24	7.80	17.20	166	6.54	126	4.96	174	6.86	181	7.13	T32
SR24-12h	12	24	7.60	16.75	175	6.90	166	6.54	125	4.93	125	4.93	T4
SR26-12	12	26	7.80	17.20	175	6.90	166	6.54	125	4.93	125	4.93	T4
SR28-12	12	28	8.00	17.64	175	6.90	166	6.54	125	4.93	125	4.93	T4

★ The specifications are subject to change without notice.



From 33Ah to 250Ah

电池型号 Battery Model	额定 电压 Nomina l voltage (V)	容量 (Ah) Ratedca pacity (Ah) 20hrs/2 5°C	重量约 Approx. weight		外观尺寸 Dimension								端子 类型 Term inal Type
			kg	lbs	长 Length		宽 Width		高 Height		Total Height		
					mm	inch	mm	inch	mm	inch	mm	inch	
SR36-6	6	36	6.50	14.33	162	6.38	88	3.47	164	6.46	177	6.97	T3
SR100-6	6	100	17.00	37.48	195	7.68	170	6.70	207	8.16	210	8.27	T16
SR180-6	6	180	29.00	63.93	260	10.24	180	7.09	246	9.69	250	9.85	T19
SR200-6	6	200	30.50	67.24	322	12.69	178	7.01	227	8.94	230	9.06	T10
SR225-6	6	225	34.50	76.06	243	9.57	188	7.41	276	10.87	276	10.87	T19
SR33-12	12	33	10.00	22.05	196	7.72	131	5.16	155	6.11	180	7.09	T16
SR35-12	12	35	10.20	22.27	196	7.72	131	5.16	155	6.11	180	7.09	T16
SR38-12	12	38	12.90	22.49	197	7.76	166	6.54	174	6.86	181	7.13	T12
SR40-12	12	40	13.00	28.66	197	7.76	166	6.54	174	6.86	181	7.13	T12
SR45-12	12	45	13.80	31.08	197	7.76	166	6.54	171	6.74	171	6.74	T9
SR50-12	12	50	16.20	35.71	230	9.06	138	5.44	211	8.31	224	8.83	T12
SR55-12	12	55	16.20	35.71	230	9.06	138	5.44	211	8.31	229	9.02	T9/16
SR60-12	12	60	19.60	42.77	350	13.79	166	6.54	179	7.05	179	7.05	T9
SR65-12	12	65	20.50	45.19	350	13.79	166	6.54	179	7.05	179	7.05	T9
SR70-12	12	70	22.00	48.50	260	10.24	169	6.66	211	8.31	224	8.83	T12
SR70-12	12	70	22.00	48.50	260	10.24	169	6.66	211	8.31	215	8.47	T16
SR80-12	12	80	26.00	54.01	329	12.96	173	6.82	213	8.39	233	9.18	T10
SR90-12	12	90	28.00	56.22	307	12.10	169	6.66	211	8.31	215	8.47	T16
SR100-12	12	100	30.00	66.14	331	13.04	173	6.82	213	8.39	233	9.18	T10
SR100-12	12	100	31.00	68.34	331	13.04	173	6.82	213	8.39	233	9.18	T10
SR100-12	12	100	32.00	71.65	407	16.04	174	6.86	209	8.23	233	9.18	T11
SR120-12h	12	120	36.50	80.47	407	16.04	174	6.86	209	8.23	233	9.18	T11
SR134-12	12	134	41.50	91.49	341	13.44	173	6.82	282	11.11	283	11.15	T19
SR150-12	12	150	42.50	93.70	484	19.07	171	6.74	241	9.50	241	9.50	T11
SR150-12	12	150	45.00	99.21	484	19.07	171	6.74	241	9.50	241	9.50	T11
SR150-12	12	150	50.00	110.23	551	21.71	110	4.33	287	11.31	287	11.31	T46
SR165-12	12	165	49.00	108.03	494	19.46	204	8.04	208	8.20	232	9.14	T11
SR180-12	12	180	55.00	121.25	560	22.06	125	4.93	316	12.45	316	12.45	T46
SR200-12	12	200	60.00	127.87	522	20.57	240	9.46	216	8.51	240	9.46	T11
SR200-12	12	200	64.00	132.28	522	20.57	240	9.46	216	8.51	240	9.46	T11
SR220-12	12	220	64.50	141.09	522	20.57	240	9.46	216	8.51	243	9.57	T11
SR250-12	12	250	73.00	160.94	520	20.49	268	10.56	220	8.67	243	9.57	T11

★ The specifications are subject to change without notice.



From 50 Ah to 3000 Ah

电池型号 Battery Model	额定 电压 Nomina l voltage (V)	容量 (Ah) Ratedca pacity (Ah) 20hrs/2 5°C	重量约 Approx. weight		外观尺寸 Dimension								端子 类型 Termi nal Type
			kg	lbs	长 Length		宽 Width		高 Height		Total Height		
					mm	inch	mm	inch	mm	inch	mm	inch	
SR50-2	2	50	2.90	6.39	160	6.30	49	1.93	166	6.54	176	6.93	T12
SR100-2	2	100	5.60	12.35	171	6.74	71	2.80	207	8.16	227	8.94	T6
SR100-2	2	100	5.90	13.01	171	6.74	71	2.80	207	8.16	231	9.09	T11
SR150-2	2	150	8.00	17.64	172	6.78	102	4.02	207	8.16	231	9.09	T11
SR200-2	2	200	13.50	29.76	172	6.78	111	4.37	329	12.96	356	14.03	T20
SR300-2	2	300	18.80	41.45	171	6.74	151	5.95	330	13.00	366	14.42	T20
SR400-2	2	400	26.70	58.86	210	8.27	176	6.93	329	12.96	366	14.42	T20
SR500-2	2	500	31.00	68.34	341	9.50	172	6.78	331	13.04	366	14.42	T20
SR600-2	2	600	38.00	83.77	301	11.86	175	6.90	331	13.04	366	14.42	T20
SR800-2	2	800	53.00	116.84	410	16.15	175	6.90	330	13.00	365	14.38	T20
SR1000--2	2	1000	63.00	138.89	475	18.72	175	6.90	330	13.00	356	14.03	T20
SR1200-2	2	1200	74.00	163.14	475	18.72	175	6.90	330	13.00	356	14.03	T20
SR1500-2	2	1500	101.00	222.66	401	15.80	351	13.83	342	13.47	369	14.54	T20
SR1800-2	2	1800	120.00	264.55	401	15.80	351	13.83	342	13.47	369	14.54	T20
SR2000-2	2	2000	132.00	291.01	491	19.35	351	13.83	343	13.51	369	14.54	T20
SR2500-2	2	2500	165.00	363.76	710	27.97	352	13.87	342	13.47	369	14.54	T20
SR3000-2	2	3000	195.00	429.90	710	27.97	352	13.87	342	13.47	369	14.54	T20

★The specifications are subject to change without notice

※GEL BATTERY

Characteristics

- Gel condition
- Minor self-discharge
- Low rate of loss of coolant
- Long service life
- Good deep charge cycle performance
- Widely working environment





Application

- UPS
- solar systems
- telecommunication/communication systems
- control systems
- power systems
- wind energy systems

电池型号 Battery Model	额定 电压 Nomina l voltage (V)	容量 (Ah) Ratedca pacity (Ah) 20hrs/2 5℃	重量约 Approx. weight		外观尺寸 Dimension								端子 类型 Termi nal Type
			kg	lbs	长 Length		宽 Width		高 Height		Total Height		
					mm	inch	mm	inch	mm	inch	mm	inch	
SRG33-12	12	33	10.40	22.93	196	7.72	131	5.16	155	6.11	170	7.09	T9、16
SRG38-12	12	38	13.50	29.76	197	7.76	166	6.54	174	6.86	181	7.13	T12
SRG50-12	12	50	17.50	38.58	230	9.06	138	5.44	211	8.31	229	9.02	T9、16
SRG55-12	12	55	17.50	38.58	230	9.06	138	5.44	211	8.31	229	9.02	T9、16
SRG65-12	12	65	23.40	51.59	350	13.79	166	6.54	179	7.05	179	7.05	T9
SRG70-12	12	70	24.20	53.35	260	10.24	169	6.66	211	8.31	215	8.47	T16
SRG100-12	12	100	34.20	75.40	407	16.04	174	6.86	209	8.23	233	9.18	T11
SRG100-12	12	100	37.00	81.57	407	16.04	174	6.86	209	8.23	233	9.18	T11
SRG150-12	12	150	47.50	104.72	484	19.07	171	6.74	241	9.50	241	9.50	T11
SRG200-12	12	200	64.50	142.20	522	20.57	240	9.46	216	8.51	240	9.46	T11

★ The specifications are subject to change without notice

※SOLAR BATTERY

Characteristics

- Long service life
- Good deep charge cycle performance
- Good resistance to corrosion and small internal resistance.
- Widely working environment



Application

- control systems
- power systems
- ups system
- telecommunications/communication systems
- wind energy systems
- Solar street light system
- solar power home syste



电池型号 Battery Model	额定电压 Nominal voltage (V)	容量 (Ah) Rated capacity (Ah) 20hrs/25°C	重量约 Approx. weight		外观尺寸 Dimension								端子类型 Terminal Type
			kg	lbs	长 Length		宽 Width		高 Height		Total Height		
					mm	inch	mm	inch	mm	inch	mm	inch	
SRD40-12	12	40	13.00	28.66	197	7.76	166	6.54	174	6.86	181	7.13	T12
SRD60-12	12	60	19.60	43.21	350	13.79	166	6.54	179	7.05	179	7.05	T9
SRD70-12	12	70	22.00	48.50	260	10.24	169	6.66	211	8.31	224	8.83	T12
SRD80-12	12	80	26.00	57.32	329	12.96	173	6.82	213	8.39	233	9.18	T10
SRD100-12	12	100	31.00	68.34	331	13.04	173	6.82	213	8.39	233	9.18	T10
SRD100-12	12	100	32.00	70.55	407	16.04	174	6.86	209	8.23	233	9.18	T11
SRD150-12	12	150	45.00	99.21	484	19.07	171	6.74	241	9.50	241	9.50	T11
SRD200-12	12	200	64.00	141.09	522	20.57	240	9.46	216	8.51	240	9.46	T11
SRD250-12	12	250	73.00	160.94	520	20.49	268	10.56	220	8.67	243	9.57	T11
SRD400-2	2	400	26.70	58.86	210	8.27	176	6.93	329	12.96	366	14.42	T20
SRD500-2	2	500	31.00	68.34	241	9.50	172	6.78	331	13.04	366	14.42	T20
SRD600-2	2	600	38.00	83.77	301	11.86	175	6.90	331	13.04	366	14.42	T20
SRD800-2	2	800	53.00	116.84	410	16.15	175	6.90	330	13.00	365	14.38	T20
SRD1000-2	2	1000	63.00	138.89	475	18.72	175	6.90	330	13.00	356	14.03	T20
SRD1500-2	2	1500	101.00	222.66	401	15.80	351	13.83	342	13.47	369	14.54	T20
SRD2000-2	2	2000	132.00	291.01	491	19.35	351	13.83	343	13.51	369	14.54	T20
SRD3000-2	2	3000	195.00	429.90	710	27.97	352	13.87	342	13.47	369	14.54	T20

※Cautions

Battery Installation Notice

- a) Lay the battery with up-down direction instead of put it inverted in any case.
- b) Abnormal vibration or shock is not allowed.
- c) Do insulate when installation.
- d) Make the batteries ventilated and gapped.
- e) Do not mix up different brand and different manufacturing date batteries.
- f) Separate the batteries from organic solvent.

UPS CATALOGUE



Guangzhou Xuntian Electronic Technology Co., Ltd.

NO.	Model	Output power capacity	type	MOQ
1	HT500	300 Watts / 500 VA	Standby	100pcs
2	HT600	300 Watts / 500 VA	Standby	100pcs
3	HT600-3F	360 Watts / 600 VA	Standby	100pcs
4	HT650-3F	390 Watts / 650 VA	Standby	100pcs
5	BK650	400 Watts / 650 VA	Standby	100pcs
6	HT800-3F	480 Watts / 800 VA	Standby	100pcs
7	HT1000-3F	600 Watts / 1000 VA	Standby	100pcs
8	HT1200-3F	720 Watts / 1200 VA	Standby	100pcs
9	HT1500-3F	900 Watts / 1500 VA	Standby	100pcs
10	SU5000	3750 Watts / 5000 VA	Line Interactive	100pcs
11	SUA750ICH	500 Watts / 750 VA	Line Interactive	100pcs
12	SUA1000ICH	670 Watts / 1000 VA	Line Interactive	100pcs
13	SUA1500ICH	980 Watts / 1500 VA	Line Interactive	100pcs
14	SUA2200ICH	1980 Watts / 2200 VA	Line Interactive	100pcs
15	SUA3000ICH	2700 Watts / 3000 VA	Line Interactive	100pcs
16	SURT3000XLICH	2100 Watts / 3000 VA	On-line	30pcs
17	SURT5000XLICH	3500 Watts / 5000 VA	On-line	30pcs
18	SURT6000XLICH	4200 Watts / 6000 VA	On-line	30pcs
19	SURT8000XLICH	6400 Watts / 8000 VA	On-line	30pcs
20	SURT10000XLICH	8000 Watts / 10 kVA	On-line	30pcs
21	SUA1000UXICH	800 Watts / 1000 VA	Line Interactive	100pcs
22	SUA2200UXICH	1980 Watts / 2200 VA	Line Interactive	100pcs
23	SUA3000UXICH	2700 Watts / 3000 VA	Line Interactive	100pcs
24	SURT3000UXICH	2100 Watts / 3000 VA	On-line	30pcs
25	SURT5000UXICH	3500 Watts / 5000 VA	On-line	30pcs
26	SURT6000UXICH	4200 Watts / 6000 VA	On-line	30pcs
27	SURT8000UXICH	6400 Watts / 8000 VA	On-line	30pcs
28	SURT10000UXICH	8000 Watts / 10 kVA	On-line	30pcs
29	SURT20KUXICH	16 kW / 20 kVA	On-line	30pcs



Company name: Guangzhou Xuntian Electronic Technology Co., Ltd

Address: Room 2106, No.609, Tianhe North Road, Guangzhou Guangdong , China

Tel:86-020-87508551

Fax:86-020-87582858

E-mail: tifayip@huamobattery.com Tifa

jessiechen@huamobattery.com Jessie

ivanhe@huamobattery.com Ivan